

# PHD 26

## BEST ROUGH TERRAIN SCISSOR LIFT FOR CRITICAL WORKSPACE

For exterior and interior use, the PH26 is the most versatile platform on the market for customers requiring height in restricted areas and exceptional traction.

- ➔ Extendable lateral side bars for extra platform
- ➔ Full height driveability
- ➔ Narrow platform
- ➔ 4 X planetary hydraulics
- ➔ Among best traction and grade climbing ability on the market, highly efficient, true mechanical four-wheel drive system



**PLAFOLIFT**  
International®





TECHNICAL DATA	PHD26	
<b>A</b> Work Height	9,75 m	32'
<b>B</b> Raised Platform Height	7,93 m	26'
<b>C</b> Lowered Platform Height	1,70 m	5'-7"
<b>D</b> Stowed Height (Rails Up)	2,46 m	8'-1"
<b>E</b> Extension Deck	1 067 mm	42"
<b>F</b> Ground Clearance	190,5 mm	7.5"
Platform Dimension (inside Dimension)	1524 x 3099 (mm)	60" x 122"
Overall Dimension (inside Dimension)	2 m x 3,7 m	79" x 144"
Capacity (Overall)	680 kg	1 500 lb
Roll out deck capacity	113 kg	250 lb
Weight	3583kg	7900 lb
Lift Time / Lower Time	26 s./30 s	26 s./30 s.
Maximum Drive Height	7,93 m	26'
Drive Speed 4 x 4	4,8 Km/h (0,5 Km/h when raised)	2,98 mph (0,31 mph when raised)
Gradeability	30 %	30 %
Maximum # of Persons	4	4
Fuel	Diesel	Diesel
Tire Size / Tire Type air filled <small>(foam filled available an option)</small>	29-12.50-15	29-12.50-15
KUBOTA engine	18.5 Kw	24.8 Hp
Fuel tank capacity	95 L	25 gal
Machine width	1,9 m	75"
Machine length	3,7 m	146"



## STANDARD FEATURES

- True mechanical four-wheel drive
- Four-wheel hydraulic brakes
- Four hydraulic stabilizers for enhanced stability on uneven surfaces
- Proportional-speed
- Up and down proportional controls
- Joystick quick disconnect
- All motion audible alarm
- Hinged railing system
- Manuel lowering emergency system
- Extendable lateral side bars for extra platform
- Cold weather start kit (battery blanket, engine heater, oil heater)
- Flashing beacon light
- Operator horn
- 110v ac outlet on platform with gfi
- Kubota diesel engine
- Forklift pockets and tie down/lift lugs
- Relay based control system
- Lanyard attachment points
- 42" roll out extension deck
- Safety support for maintenance
- Hourmeter
- Better Serviceability - Fully accessible hydraulic and engine compartments



Control panel



Diesel Motor



Stabilizer



110v ac outlet on platform